


PAR64

Halogen lamps with parabolic reflector PAR64, with pin base



Product family datasheet



Product line drawing

Product family datasheet

Technical data

| Product description | Electrical data | Photometrical data | | Light technical data | Dimensions & weight | | Lifespan | Additional product data | Capabilities |
|---------------------------------|-----------------|--------------------|-------------------|----------------------|---------------------|----------|----------|-----------------------------|--------------------|
| | Nominal voltage | Luminous intensity | Color temperature | Beam angle | Diameter | Length | Lifespan | Base (standard designation) | Burning position |
| PAR64 64738/4 NSP ¹⁾ | 240 V | 270000 cd | 3200 K | 14/10 ° | 204.0 mm | 152.4 mm | 300 h | GX16d | hs30 ³⁾ |
| PAR64 64739/4 MFL ²⁾ | 240 V | 125000 cd | 3200 K | 24/11 ° | 204.0 mm | 152.4 mm | 300 h | GX16d | hs30 ³⁾ |

¹⁾ Beam angle: NSP = narrow spot

²⁾ Beam angle: MFL = medium flood

³⁾ Do not tilt perpendicular to the filament

Product family datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.